



# Premium-6 Hexagonal Wire Netting

## PRODUCT DESCRIPTION

Kiwi-made quality that's stronger, longer-lasting, and great to work with.

This high quality NZ made hexagonal wire netting is built to last. Its heavy, 150g/m<sup>2</sup>

galv coating enhances rust resistance and durability, increasing the usable life up to 6 times over light galv netting.

## SIZE RANGE AVAILABLE

Product Code	Width (mm)	Mesh (mm)	Wire Diameter (mm)	Length (m)	Area (m) <sup>2</sup>	Weight (kg)	Barcode
HN200075150P6	2000	75	1.0	50	100	19.00	9421026721983
HN200075125P6	2000	75	1.0	25	50	9.50	9421026721969
HN90075150P6	900	75	1.0	50	45	9.50	9421026722225
HN200050150P6	2000	50	1.0	50	100	29.67	9421026721952
HN200050125P6	2000	50	1.0	25	50	14.67	9421026721945
HN180050150P6	1800	50	1.0	50	90	26.33	9421026721938
HN180050125P6	1800	50	1.0	25	45	13.50	9421026721921
HN150050150P6	1500	50	1.0	50	75	22.67	9421026721860
HN120050150P6	1200	50	1.0	50	60	18.33	9421026721846
HN90050150P6	900	50	1.0	50	45	14.00	9421026722218
HN90050110P6	900	50	1.0	10	9	2.67	9421026722195
HN9005015P6	900	50	1.0	5	4.5	1.33	9421026722201

We also stock a full range of 41mm hexagonal wire netting. Please refer to the Bayonet Premium-6 Rabbit Netting brochure for details.

HN120025150P6	1200	25	1.0	50	60	37.50	9421026721822
HN90025150P6	900	25	1.0	50	45	29.33	9421026722126
HN90025110P6	900	25	1.0	10	9	5.50	9421026720023
HN9002515P6	900	25	1.0	5	4.5	2.83	9421026720030
HN90019150P6	900	19	1.0	50	45	35.33	9421026722089
HN90019110P6	900	19	1.0	10	9	6.50	9421026720047
HN9001915P6	900	19	1.0	5	4.5	3.67	9421026720054

## FEATURES

- Wire tensile strength is between 380 and 550 MPa.
- Heavy 150g/m<sup>2</sup> galv coating improves durability and rust resistance, delivering up to 6 times longer life than light galv netting.
- Commonly used for dog or chicken runs, pet cages, aviaries, fencing, general garden use, and anti-slip for boardwalks.
- Also available in a 41mm mesh ideal for Rabbit fencing (please refer to the Bayonet Premium-6 Rabbit Netting brochure).
- Twin edge wires for ease of tensioning (75mm and 50mm netting only).
- Supersized core for reduced wastage (currently available for 75mm netting only).
- Galvanising complies with AS/NZS 4534: 2006 Class W10.
- Netting complies with NZS 4251: 2007.
- Manufactured in New Zealand using some of the best raw materials.

