

**DESCRIPTION**

A synthetic self-supporting roofing underlay for use under roof claddings. It consists of a micro-porous water-resistant film, laminated to two layers of non-woven spun-bonded polyolefin. It is black on the top face, white on the bottom face and is printed with laying lines.

**FEATURES**

- Stronger and more resistant to shrinkage than conventional self-supporting kraft paper underlays
- Water resistant and will not rot
- May be installed in wet conditions without affecting its surface
- Breathable water-resistant film reduces the risk of condensation.

**SCOPE OF USE**

- The scope limitations of NZBC Acceptable Solution E2/AS1, Paragraph 1.1 with regards to building height and floor plan area
- In wind zones under NZS 3604:2011 up to and including 'Extra high'
- Unsupported to a span of 1200mm
- For use in both timber and steel framed roofs
- With masonry tile, metal tile and profiled metal roof cladding

**APPRAISALS**

- BRANZ appraisal No. 984 [2017]

**LIMITATIONS OF USE**

- Should not be exposed for longer than 7 days.
- Where fire protection is required – we recommend Fastwrap FlameSpec SS Synthetic Roof Underlay.
- Must not be used under translucent sheeting.

**PERFORMANCE**

- Meets the requirements of NZBC B2.3(c) 15 years (durability)
- Meets the requirements of NZBC E2/AS1, Table 23 (surface absorbency)

Installation according to manufacturer's instructions.

**WARRANTY**

- 15 years

**MAINTENANCE**

- No maintenance requirements

## STORAGE

- Stand on end in dry conditions. Protect from weather and direct sunlight.

## SIZE RANGE AVAILABLE

Width (mm)	Length (m)	Total (m <sup>2</sup> )	Weight (kg)
1250	40	50	8.93
1500	34	50	8.93